

	Key
	Construct Footway Type F1 to standard detail CS/SD11/28A.
	Carriageway to be reinstated using an A2 patch to standard detail C9 A1/A.
	Install K3/1 Bullnose kerb (flush) to standard detail CS/SD11/03.
	Install K5 Transition kerb to standard detail CS/SD11/04.
	Install E1 Edge kerb to standard detail CS/SD11/14.
	Existing concrete Half-batter kerb.
	<ul> <li>Install BUFF coloured blister tactile paving to standard detail CS/SD11/53.</li> </ul>

carriageway "B" class road with 30 mph. nderground services - see attached Public Utility plans. Irawn. her services present and the Contractor shall take sures to locate them.								
e 75 mm high and to standard detail CS/SD11/38. gles to be marked as shown to Dia. 1062. o be laid in white thermoplastic screed and reflectorised in accordance with Table 12-1 of TSM Chapter 5 2019. to standard detail CS/SD11/37. to and Foundation Design for 20 zone signs. be minimum 0.45 m from carriageway edge. aterials where possible. als to be removed to tip off site.								
MENTS		BY	AP'D	DATE				
struction ngry	Fife T	RANS	DADS PORT RVIC	ATION				

00408		HEAD OF SERVICE - JOHN MITCHELL				
ECKED	LC	APPROVED	LC	DATE	APRIL 2024	